

# Trolley Fire Extinguishers

**Chubb** Trolley fire extinguishers are used to provide additional protection to high-risk areas. These trolley extinguishers are easily handled by one person and can be filled with ABC Dry Powder, AFFF FOam, Carbon Dioxide, Halotron™ I depending on the usage.



25kg ABC Stored Pressure



45ltr AFFF Foam Stored Pressure



50kg ABC Cartridge



75kg ABC Cartridge



25kg Carbon Dioxide



50kg Halotron™ I

## ABC DRY POWDER TROLLEY

Capacity	25kg	50kg	75kg	50kg	75kg	100kg	150kg
Chemical Extinguishant	ABC Dry Chemical Powder						
Propellant Type	Stored Pressure			Carbon Dioxide Gas Bottle with Screw Down Valve			
Class of Fire	A, B, C & Electrical						
Working Temperature	-20°C to +60°C						
Test Pressure	31 kgf/cm <sup>2</sup>				35 kgf/cm <sup>2</sup>		
Working Pressure	15 kgf/cm <sup>2</sup>		18kgf/cm <sup>2</sup>	15kgf/cm <sup>2</sup>	18kgf/cm <sup>2</sup>	20kgf/cm <sup>2</sup>	
Height (Mm)	895	935	1190	940	1190	1190	1300
Depth (Mm)	540	685	740	670	740	740	810
Width (Mm)	410	500	590	500	590	590	770
Approx. Empty Weight (Kg)	20	35	52	44	67	71	104
Approx. Full Weight (Kg)	45	85	127	94	142	171	254
Min. Discharge Range (M)	10	14	14	14	14	16	16
Min. Discharge Time (Sec)	40	45	55	45	55	76	68
CO <sup>2</sup> Gas Bottle Size				1.5kg	2.0kg	2.3kg	3.5kg
Discharge Hose (M)	4	6				8	
Safe Operating Range (M)	6						
Operating Valve	Brass Quick Release Control Valve on Hose			Brass Gas Bottle Valve & Control Valve on Hose			
Paint Finish	Red						

## CARBON DIOXIDE & FOAM TROLLEY

Capacity	25 ltr	45 ltr	45 ltr	135 ltr	9kg	15kg	25kg	45kg
Chemical Extinguishant	3% AFFF Foam				Carbon Dioxide			
Propellant Type	Stored Pressure		CO <sup>2</sup> Gas Bottle with Screw Down Valve		Stored Pressure			
Class of Fire	A & B				B, C & Electrical			
Working Temperature	+5°C to +60°C				-20°C to +60°C			
Test Pressure	31 kgf/cm <sup>2</sup>			35 kgf/cm <sup>2</sup>	Min 200 kgf/cm <sup>2</sup>			
Working Pressure	15 kgf/cm <sup>2</sup>			20kgf/cm <sup>2</sup>	60kgf/cm <sup>2</sup>			
Height (Mm)	895	953	940	1400	1000	1000	1430	1600
Depth (Mm)	540	685	670	700	320	400	540	640
Width (Mm)	410	500	500	600	360	410	600	730
Approx. Empty Weight (Kg)	20	35	42	104	36	50	70	100
Approx. Full Weight (Kg)	45	80	87	239	45	65	95	145
Min. Discharge Range (M)	14	15	15	16	Min 4 metres			
Min. Discharge Time (Sec)	60	95	95	235	24	36	41	75
CO <sup>2</sup> Gas Bottle Size	Not Applicable		1.0kg	3.5kg	Not Applicable			
Discharge Hose (M)	4			6	Hose & Horn	6		
Safe Operating Range (M)	6				2			
Operating Valve	Quick Release Valve & Control Valve on Hose				Gas Bottle Valve	Gas Bottle Valve & Control Valve on Hose		
Paint Finish	Red							

## HALOTRON™ I TROLLEY

Capacity	30kg		50kg		68kg	
Chemical Extinguishant	Halotron™ I					
Propellant Type	Stored Pressure					
Class of Fire	A, B, C & Electrical					
Working Temperature	-20°C to +60°C					
Test Pressure	25 kgf/cm <sup>2</sup>					
Working Pressure	8.63kgf/cm <sup>2</sup>					
Height (Mm)	935		1190		1190	
Depth (Mm)	685		740		740	
Width (Mm)	500		590		590	
Approx. Empty Weight (Kg)	35		52		52	
Approx. Full Weight (Kg)	65		102		120	
Min. Discharge Range (M)	4.5 - 7.5		5.5 - 8.5		7.5 - 10	
Min. Discharge Time (Sec)	17		19		23	
CO <sup>2</sup> Gas Bottle Size	Not Applicable					
Discharge Hose (M)	6					
Safe Operating Range (M)	6					
Operating Valve	Quick Release Control Valve					
Paint Finish	Red					

The company reserves the right to change the specification without prior notice.

**To purchase Chubb fire extinguishers or request further information, please contact us at**

Chubb Singapore Pte Ltd  
 207 Kallang Bahru Singapore 339343  
 Tel: +65 6292 8421 Fax: +65 6298 7310  
 Website: www.chubb.com.sg Email: sales@chubb.com.sg

